

Technical Data SE series

MODEL	SE-10/3	SE-11/3	SE-12/3	SE-13/3	SE-14/3	SE-15/3	SE-16/3	SE-17/3	SE-18/3	SE-19/3	SE-20/3	SE-21/3	SE-22/3	SE-23/3
Power - kVA	3	5	7.5	10	15	20	25	30	40	50	60	75	100	150
Input														
Phases	Threephase + N													
Voltage	400 V -30% +20%													
Frequency	50 Hz													
Output														
Wave-form	SINE WAVE													
Harmonic distortion	No induced distortion													
Voltage	400 V \pm 3%													
Frequency	50 Hz													
Efficiency at full load	98%													
Intervention time	2 ms for any voltage variation													
Voltage variations from 0 to full load	None													
Attenuation of mains disturbances	At 0.1 MHz 50 dB, at 1 MHz 55 dB, at 100 MHz 70 dB													
Test voltage between line and mass	2250 V													
Signals														
LED	Input; Output; Min/Max Input Voltage													
Voltmeter in input and output	Standard													
Environmental														
Temperature	-22°C ÷ 50°C													
Non-condensing humidity	0% ÷ 90%													
Cooling	Forced													
Dimensions														
W x D x H - mm	500 x 250 x 740				600 x 300 x 850				800 x 400 x 1050		800 x 400 x 1450		800 x 600 x 2000	
Weight - kg	35	43	53	62	78	100	110	120	190	205	300	400	500	700
CE Marking	EEC 73/23; EEC 89/336; EEC 92/31													
Compliance with the standards	IEC 742													



Factory - Head Office

S. P. km 5,300 C/da San Cusumano - 91100 Trapani - Italy

Tel. +39 0923 562794 - Fax +39 0923 567880 - Http://www.layer.it - E-mail: layer@layer.it