

Technical Data UC series

MODEL	UC-1	UC-2	UC-3	UC-4	UC-5	UC-6	UC-7	UC-8	UC-9
Power - kVA	0.5	1	1.5	2	3	4	5	7.5	10
Input									
Phases	Monophase (Threephase + N upon request)								
Voltage	230 V (400 V upon request) \pm 20%								
Frequency	50 Hz \pm 5%								
Output									
Voltage	Upon request								
Ripple	< 2%								
Overload	110% for 1 h								
Batteries									
Type	Sealed lead-acid								
Charge control	automatic with electronic control								
Restored energy time	< 4 hours								
Stored energy time - min	Upon request								
Protections									
Short-circuit	With electronic protection								
No-fuse breaker	Mains								
Signals									
Led	Mains, output								
Voltmeter	Output								
Ampmeter	Output								
Environmental									
Temperature	0°C ÷ 50°C								
Non-condensing humidity	0% ÷ 90%								
Noise (at 1 m)	< 40 dBA								
Dimensions									
W x D x H - mm	Request technical data								
CE Marking	EEC 73/23; EEC 89/336; EEC 92/31								
Compliance with the standards	IEC 478-1; IEC 478-2; IEC 478-4								



Factory - Head Office

S. P. km 5,300 C/da San Cusumano - 91100 Trapani - Italy

Tel. +39 0923 562794 - Fax +39 0923 567880

Http://www.layer.it - E-mail: layer@layer.it