

Technical Data UC series

MODEL	UC-1	UC-2	UC-3	UC-4	UC-5	UC-6	UC-7	UC-8	UC-9	UC-10	UC-11	UC-12	UC-13	UC-14	UC-15	UC-16
Power - kVA	0.5	1	1.5	2	3	4	5	7.5	10	12.5	15	20	25	30	40	50
Input																
Phases	1-Ph / 3-Ph + N															
Voltage	220 / 230 / 240 Vac // 380 / 400 / 415 Vac \pm 20% (100 / 110 / 115 / 120 / 127 Vac // 200 / 208 / 220 / 440 / 480 Vac on request)															
Frequency	50 / 60 Hz \pm 5%															
Output																
Voltage	24 / 36 / 48 / 72 / 110 / 150 / 220 / 400 Vdc															
Ripple	$<$ 2%															
Overload	110% for 1 h															
Batteries	Optional															
Type	Sealed lead-acid (NiCd / Li-Ion / NaNiCl ₂ on request)															
Charge control	Automatic with electronic control															
Stored energy time - min	Upon request															
Protections																
Short-circuit	With electronic protection															
No-fuse breaker	Mains															
Signals																
Led	Mains, output															
Voltmeter	Output															
Ammeter	Output															
Environmental																
Temperature	0°C \div 50°C															
Non-condensing humidity	0% \div 95%															
Noise (at 1 m)	$<$ 40 dBA															
Protection rating	IP20															

UC Dimensions																
W x D x H - mm	400 x 250 x 540		400 x 250 x 640		500 x 250 x 740		600 x 400 x 840		600 x 400 x 1050			800 x 400 x 1050			800 x 400 x 1250	
UC Weight - kg	20	35	45	60	70	80	90	120	140	150	160	200	240	300	340	360
CE Marking	2014/30/EU; 2014/35/EU															
Compliance with the standards	IEC 478-1; IEC 478-2; IEC 478-4															



Factory - Head Office

S.P. km 5,3 C/da San Cusumano - 91100 Trapani - Italy

Tel. +39 0923 562794 - Fax +39 0923 567880

Http://www.layer.it - E-mail: layer@layer.it